



USB-AM SOLDER TAIL  
焊线式

特性: Specifications

电器 Electrical:

接触阻抗: Contact Resistance

30milliohms MAX

耐电压: Dielectric Withstanding Voltage

500V DC AT sea LevoL

绝缘阻抗: Insulation Resistance:

100MEGA ohms MIN

材料: Material:

塑胶: Housing:Hing Temperature Thermoplastics,  
PP料白塑胶

端子: Contact:Copper Alloy 铜合金

铁壳: Shell:SPCC-SD 铁

电镀: Finish:

端子: Contact: Plated Gold in Mating Area;

Tin/Lead On Solder Talls

接触点镀金, 脚镀锡铅

铁壳: Shell:

Tin/Lead Piating 镀镍

Ordering Informating

X-5-XX

contact plating  
01-Gold Flash  
02-1-3u"Gold/Tin  
03-30u"Gole/Tin

X  
Plastic Color  
A=Black

深圳市金航标电子有限公司		WWW.BDS666.COM	单位 (Unit) :MM
KH-USB-AM-2712		0755-83044319	比例 (Scale) 1:1
品名 (Commodity):	USBA公(长体) 焊线式 (平口)		ANGLE OF PROJECTION 未注公差 Tolerance Unspecified
审核 (CHECKED):	版本 (REV):	A/0	X.X ± 0.30 X.XX ± 0.20 X.XXX ± 0.10 X° ±5° XX° 2°
设计 (DESIGN):	朱世辉	日期 (DATE):	2011/1/5

NO.	Part Name	Material	Color/Plating	REMARK
3	Shell	SPCC or St30 1x0.20mm	1	See Order Information
2	Housing	Thermoplastic PP	1	See Order Information
1	Contact	Tin/0.20mm SPCC		Gold Flash on Contact And Tin on Tail