


SCHEMATIC



SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance : $\leq 0.03\Omega$;
3. Insulation resistance : $\geq 100M\Omega$ (DC250V);
4. Withstand voltage : 500VAC ;
5. Insertion and extraction force : 3-25N;
6. life test : 5,000 cycles.

						容许公差 GENERAL TOLERANCE		深圳市金航标电子有限公司		www.kinghelm.com.cn	
						X. X	±0.1	KH-PJ-301M		0755-28190160	
						X. XX	±0.05	型号: Model: 耳机插座 PJ-301M			
						X. XXX	±0.005				
						角度公差 ANGLE TOLERANCE		料号: Part Number:			
						X. °	±5.0°				
						X. X°	±3.0°	单位 UNIT		张数 SHEET	
						X. XX°	±1.0°	mm		1/1	
5	HOUSING	ABS	1					比例 SCALE		版本 REV	
4	AXIS SUPPORT	H62 BRASS	1	Ni-Plating	修正 REVISION			4:1		A	
3	SPRING PIECE	PHOSPHOR BRONZE	1	Cu-Sn-Plating	绘制 DRAWN 15-6/12						
2	CURVE PIECE	H62 BRASS	1	Su-Sb-Plating	设计 DES' D 15-6/12						
1	FLAT PIECE	H62 BRASS	1	Cu-Sn-Plating	校对 CHK' D 15-6/12						
序号	名称	材料	数量	镀层/颜色	核准 APP' D 15-6/12						